

AT 202 - FINISH RESTORER

APPLICATION INSTRUCTIONS

1. PRODUCT DESCRIPTION

AT 202 - Finish Restorer removes oxidation and other surface debris and spots without the use of harsh abrasives. It is an easy way to bring back the luster to dulled finishes without the use of power buffers. AT 202 is excellent for use on automobiles, boats, trains, aircraft, tractors, outdoor equipment, and metal building facades. It is environmentally safe and may be used in and around US waterways.

2. APPLICATION

- As with any new material, always test application and finished properties on a low value test article or panel before working on valuable surfaces.
- Apply AT 202 to a water dampened clean terry-cloth towel.
- Use overlapping circles to evenly spread the product over the surface.
- If the product starts to dry out, mist a little water over the surface before continuing to work the product over the surface using a circle motion.
- To inspect the surface for the quality of the gloss, rinse off with water and then use a clean washcloth to lightly buff the surface. Use a soft cloth with gentle pressure so as not to scratch the finished surface.
- If the gloss surface is not uniform, just apply more of the product to that area using the same technique as above.
- Once the finish is uniform, rinse off with water and dry with a soft, clean towel.
- A sealing top coat such as AT 303 or AT 5000 should be applied to create long-term protection.

3. STORAGE STABILITY& SHELF LIFE

The shelf life is one year when stored in the original, unopened container. Store containers in a well-ventilated and covered area away from extreme heat and moisture. Contact your ALPHATEK representative if you have any questions about the products or its uses.

4. SAFETY

Refer to the Safety Data Sheet for this product prior to use.