

# AT 303 - PREMIUM POLYMER POLISH

## APPLICATION INSTRUCTIONS

### 1. PRODUCT DESCRIPTION

AT 303 - Premium Polymer Polish is an ultra high performing polish that protects almost any painted surface. It applies easily to virtually all painted, powder coated, plastic and polished surfaces to create a beautiful and long lasting shine. It may be applied and hand buffed in direct sunlight. AT 303 lasts longer than most wax products and a single treatment will last for a season in most conditions. AT 303 is often used on automobiles but it is also very effective on boats, tractors, airplanes, outdoor equipment and metal building facades.

### 2. APPLICATION

- As with any new material, always test application and finished properties on a low value test article or panel before working on valuable surfaces.
- Wash and dry the surface before polishing. AT 101 is an excellent option for cleaning almost any surface. AT 303 will remove road tar, bird droppings, and bugs during application.
- If surface is oxidized/rusted, use AT 202 to treat the surface prior to applying AT 303.
- Product may be applied in the shade or in direct sunlight.
- Shake bottle well.
- Apply modest amount of polish to a soft clean towel or soft foam sponge and then rub on to the desired surface.
- Let dry to a haze.
- Buff to a high gloss with a soft clean towel.

### 3. STORAGE STABILITY& SHELF LIFE

The shelf life is one year when stored in the original, unopened container. Store containers in a well-ventilated and covered area away from extreme heat and moisture. Contact your ALPHATEK representative if you have any questions about the products or its uses.

### 4. SAFETY

Refer to the Safety Data Sheet for this product prior to use.